

Getac

Rugged Mobile Computing Solutions

F110

Fully Rugged Tablet



- Enhanced Enterprise Security with optional Intel vPro, Windows Disk Encryption, TPM 2.0 and many more multi-factor authentication options
- 6th Generation Intel® Core™ i7/i5 vPro™ Processor
- 11.6" LumiBond® 2.0 Display with Getac Sunlight Readable Technology and Capacitive Touchscreen
- 5 Customizable Configurations to Fit Your Need (Optional 1D/2D Imager Barcode Reader/Serial Port/Ethernet/MicroSD/2nd USB 2.0 Port)
- LifeSupport™ Battery Swappable Technology



Office Dock





Specifications

Model Name	F110 G3	Communication Interface	Optional 10/100/1000 base-T Ethernet ⁱ (occupies expansion slot) Intel® Dual Band Wireless-AC 8260, 802.11ac Bluetooth (v4.2) ⁱⁱ Optional dedicated GPS Optional Gobi™ mobile broadband
Operating System	Windows 10 Professional Windows 7 Professional	Software	Getac Utility (including Power Manager) Getac Camera Getac Geolocation Getac Barcode Manager Adobe® Reader®
Mobile Computing Platform	Intel® Core™ i7 Technology Intel® Core™ i7-6500U Processor 2.5GHz Max. 3.1GHz with Intel® Turbo Boost Technology - 4MB Intel® Smart Cache Intel® Core™ i7 vPro™ Technology Option Intel® Core™ i7-6600U vPro™ Processor 2.6GHz Max. 3.4GHz with Intel® Turbo Boost Technology - 4MB Intel® Smart Cache Intel® Core™ i5 Technology Intel® Core™ i5-6200U Processor 2.3GHz Max. 2.8GHz with Intel® Turbo Boost Technology - 3MB Intel® Smart Cache Intel® Core™ i5 vPro™ Technology Optional Intel® Core™ i5-6300U vPro™ Processor 2.4GHz Max. 3.0GHz with Intel® Turbo Boost Technology - 3MB Intel® Smart Cache	Security Feature	Intel® vPro™ Technology TPM 2.0 Optional RFID ⁱⁱⁱ , iv Magnetic Stripe reader, Smart Card reader or fingerprint scanner, ^v Kensington lock
VGA Controller	Intel® HD Graphics 520	Power	AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-Ion smart battery (11.4V, 2160mAh) x 2 (up to 12 hours of battery life) ^{vi} LifeSupport™ battery swappable technology
Display	11.6" TFT LCD HD (1366 x 768) 800 nits LumiBond® display with Getac sunlight readable technology Capacitive multi-touch screen	Dimension (W x D x H) & Weight	314 x 207 x 24.5 mm (12.4" x 8.15" x 0.96"), 1.39 kg (3.08 lbs) ^{vii}
Storage & Memory	4GB DDR4 expandable to 16GB SSD 128GB / 256GB / 512GB	Rugged Feature	MIL-STD-810G certified and IP65 certified MIL-STD-461F certified ^{viii} Optional ANSI/ISA 12.12.01 Vibration & drop resistant e-Mark certified for vehicle usage
Keyboard	6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)	Environmental Specification	Temperature ^{ix} : - Operating: -21°C to 60°C / -5.8°F to 140°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH , non-condensing
Pointing Device	Touchscreen - Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)	Optional Accessories	Carry bag Battery charger Multi-bay charger (Dual Bay) Multi-bay charger (Eight Bay) Detachable folding keyboard Vehicle adapter (90W, 11-16VDC and 22-32VDC) MIL-STD-461F certified AC adapter (90W, 100-240VAC) Digitizer pen Capacitive stylus (Hard-tip) Protection film Tablet folio case Hand-strap Shoulder harness (4-point; handsfree) Shoulder strap (2-point) Battery (11.4V, 2160mAh) AC adapter (65W, 100-240VAC) Vehicle cradle Vehicle dock Office dock Office dock with twin battery charger
Expansion Slot	Optional 1D/2D Imager Barcode Reader, Serial Port, Ethernet, MicroSD or 2 nd USB 2.0 Port ⁱ		
I/O Interface	FHD webcam x 1 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.0 (9-pin) x 1 Docking connector (24-pin) x 1 HDMI x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN		

Docking Solutions

	Serial Port	External VGA	Microphone	Audio Output	DC in Jack	USB	LAN	HDMI	RF Antenna Connector (GPS, WWAN, WLAN)
Vehicle Dock	2	1	1	1	1	4	1	1	3
Office Dock	2	1	1	1	1	4	1	1	--

i Barcode reader, Serial port, Ethernet, MicroSD or 2nd USB 2.0 port are mutually exclusive options.

ii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

iii RFID, Magnetic Stripe reader, Smart card reader are mutually exclusive options.

iv 13.56MHz Contactless RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).

v Windows 7 and Windows 10 only.

vi Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions.

The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

vii Weight varies from configurations and optional accessories.

viii MIL-STD-461F 90W AC adapter sold separately.

ix Tested by a national independent third party test lab following MIL-STD-810G.

Getac

Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist.,
Taipei City, 11568, Taiwan, R.O.C.

Tel: +886 2 2785 7888

globalmarketing@getac.com

www.getac.com



Copyright © 2016 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.

Information provided herewith is for reference only,

available specification shall be subjected to quotation by request. V02M09Y16WWW