



X500 FULLY RUGGED NOTEBOOK

- Intel® Core™ i7-7820HQ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® Sunlight Readable Display
- Optional NVIDIA® GeForce® GTX1050 4GB Discrete Graphic Controller
- Multimedia Bay & PCI/PCIe 3.0 Expansion Unit



PCI/PCI-Express 3.0
Expansion Unit



Multimedia Bay
2nd Storage



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i7-7820HQ 2.9GHz, Max. 3.9GHz

- 8MB Intel® Smart Cache

Intel® Core™ i5-7440HQ 2.8GHz, Max. 3.8GHz

- 6MB Intel® Smart Cache

VGA Controller

Intel® HD Graphics 630

Optional NVIDIA® GeForce® GTX1050 4GB

discrete graphic controller

Display

15.6" TFT LCD FHD (1920 x 1080)

1000 nits QuadraClear® sunlight readable display

Optional resistive touch screen

Storage & Memory

Optional 8GB / 16GB / 32GB / 64GB DDR4ⁱ

Optional SATA HDD 500GB / 1TB;

SATA SSD 512GB / 1TB

Keyboard

LED backlit membrane keyboard with

integrated numeric keypad

Optional LED backlit rubber keyboard

Pointing Device

Touchscreen

- Optional pressure sensitive touchscreen

Touchpad

- Glide touchpad with scroll bar

Expansion Slot

Optional PCMCIA Type II x 1

ExpressCard/54 x 1

Smart Card reader x 1

SD Card Reader x 1

Multimedia Bay

DVD super multi drive

Optional 2nd battery: 10.8V, 8700mAh

Optional 2nd storage: HDD 500GB / 1TB ;

SSD 512 GB / 1TB

I/O Interface

Serial port (9-pin; D-sub) x 2

External VGA (15-pin; D-sub) x 1

Microphone (Mini-jack) x 1

Audio output (Mini-jack) x 1

DC in Jack x 1

USB 3.0 x 4

LAN (RJ45) x 2

HDMI x 1

Docking connector x 1

Optional RF antenna pass-through for GPS^j,

WLAN and WWAN

Optional FHD webcam x 1

Communication Interface

10/100/1000 base-T Ethernet

Intel® Dual Band Wireless-AC 8265, 802.11ac

Bluetooth® (v4.2)^j

Optional dedicated GPS

Security Feature

Intel® vPro™ Technology

TPM 2.0

Smart Card reader

Kensington lock

Power

AC adapter (150W, 100-240VAC, 50 / 60Hz)

Li-Ion smart battery (10.8V, typical 8700mAh;

min. 8100mAh)

Optional Multimedia Bay 2nd Li-Ion smart battery

(10.8V, typical 8700mAh; min. 8100mAh)

Dimension (W x D x H) & Weight

410 x 320 x 65mm (16.1" x 12.6" x 2.5")

5.2 kg (11.4 lbs)^v

Rugged Feature

MIL-STD-810G certified and IP65 certified

MIL-STD-461G certified^v

Optional ANSI/ISA 12.12.01^{vi}

Full magnesium alloy case

Shock-protected removable HDD

Vibration & drop resistant

Environmental Specification

Temperature^{vii}:

- Operating: -20°C to 55°C / -4°F to 131°F

- Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

Software

Getac Utility

Getac Geolocation

Optional Absolute DDS® Persistence

Accessories

Backpack

Multi-Bay Charger (Dual Bay)

MIL-STD-461 certified AC adapter (150W, 100-240VAC)

Stylus

Protection film

PCI or PCI-Express 3.0 Expansion Unit (x 2 slots)^{viii}

Main battery (10.8V, typical 8700mAh; min.

8100mAh)

AC adapter (150W, 100-240VAC)

Multimedia bay 2nd battery (10.8V, typical 8700mAh;

min. 8100mAh)

Multimedia Bay 2nd HDD

Vehicle dock^{viii}

Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

5 years Bumper-to-Bumper

- i Share memory size may vary by different operating system and RAM size.
- ii Optional RF antenna pass-through for GPS, PCI or PCI-Express Expansion Unit are mutually exclusive options.
- iii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iv Weight and dimensions vary from configurations and optional accessories. Depth including hard handle.
- v MIL-STD-461G 150W AC adapter sold separately.
- vi PCI or PCI-Express 3.0 Expansion Unit is not available with ANSI / ISA 12.12.01 configurations.
- vii Tested by a national independent third party test lab following MIL-STD-810G.
- viii PCI or PCI-Express 3.0 Expansion unit is not compatible with vehicle dock.

X500

Fully Rugged Notebook



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	2	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 4	USB 2.0 x 2 USB 3.0 x 2
LAN	1	1
RF Antenna Connector	3 (optional)	--

Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,

Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.

Tel : +886 2 2785 7888

globalmarketing@getac.com | www.getac.com



Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M04Y20WW