



# K120 FULLY RUGGED TABLET


- 11th Generation Intel<sup>®</sup> Core<sup>™</sup> i7 / i5 vPro<sup>™</sup> Processor
- 12.5" FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,200 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro, Windows Hello face-authentication camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport™ Battery Swappable Technology
- Thunderbolt<sup>™</sup> 4 brings lightning speed and performance











## **Specifications**

## Operating System Windows 10 Pro

Mobile Computing Platform Intel® Core™ i5-1135G7 Processor Max. 4.2GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

- 8/MB Intel® Smart Cache
Platform Options:
Intel® Core™ i5-1145G7 vPro™ Processor
Max. 4.4GHz with Intel® Turbo Boost Technology
- 8/MB Intel® Smart Cache
Intel® Core™ i7-1165G7 Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 12/MB Intel® Smart Cache

Intel® Core™ i7-1185G7 vPro™ Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

## **VGA Controller**

Intel® Iris® Xe Graphics

## **Display**

Protection film 12.0" IPS TFT LCD FHD (1920 x 1080) Protection film 1200 nits LumiBond® display with Getac sunlight readable

Capacitive multi-touch screen

## **Storage & Memory**

16GB DDR4 Optional: 32GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

## Power button

5 tablet programmable buttons

## **Pointing Device**

**Keyboard** 

- Touchscreen
   Capacitive multi-touch screen
   Optional: Dual mode touchscreen (multi-touch and digitizer)

**Expansion Slot**Optional: 1D / 2D imager barcode reader
Optional: Serial port (9-pin; D-sub), or USB 2.0 port

## I/O Interface

TABLETTACE
Tablet:
FHD webcam x 1<sup>x</sup>
8M pixels auto focus rear camera x 1
Headphone out / mic-in combo x 1
DC in Jack x 1
USB 3.2 Gen 2 Type-A x 1
Thunderbolt\*\* 4 x 1
AN (PUES x 1 LAN (RJ45) x 1 HDMI x 1 Docking connector x 2
Optional: Windows Hello face-authentication
camera (front-facing) x 1\*
RF antenna pass-through for GPS, WLAN and WWAN

Optional Keyboard Dock:

DC in Jack x 1 USB 3.2 Gen 1 Type-A x 3 LAN (RJ45) x 1 Davious 3/X i HDMI x 1 Display Port 1.2 x 1 Serial port (9-pin; D-sub) x 1 Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface
Intel® Wi-Fi 6 AX201, 802.11ax
10/100/1000 base-T Ethernet
Bluetooth (v5.2)
Optional: Dedicated GPS®
Optional: 4G LTE mobile broadband with
integrated GPS®

## **Security Feature**

TPM 2.0

IPM 2.0 Kensington Lock Optional: Intel® vPro™ Technology Optional: Smart Card reader or HF RFID reader<sup>i, ii</sup> or fingerprint reader<sup>iv</sup>

AC adapter (90W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 LifeSupport™ battery swappable technology Optional: High capacity battery (14.4V, typical 3450mAh; min. 3300mAh) x 2

## Dimension (W x D x H) & Weight

**Tablet:** 329.5 x 238 x 24 mm (12.97" x 9.37" x 0.94") 1.7Kg (3.75lbs)<sup>v</sup>

Tablet+Optional Keyboard Dock: 340.5 x 307.5 x 47 mm (13.40" x 12.10" x 1.85") 3.13Kg (6.9lbs)<sup>v</sup>

Rugged Feature
MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified
MIL-STD-461G certified
Vibration & 6 feet (1.8m) drop resistant e-Nark certified for vehicle usage
Optional: ANSI / UL 121201, CSA C22.2 NO. 213

## **Environmental Specification**

Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH , non-condensing

## **Pre-installed Software**

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager<sup>xi</sup> Optional: Absolute Persistence<sup>®</sup>

### Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh) AC Adapter (90W, 100-240VAC) Capacitive Stylus

### Optional:

Optional:
Cary Bag
Battery (11.1V, typical 2100mAh; min. 2040mAh)
High Capacity Battery (14.4V, typical 3450mAh;
min. 3300mAh)
Multi-Bay Charger (Dual Bay)
Multi-Bay Charger (Eight-Bay)
AC Adapter (90W, 100-240VAC)
Office Dock AC Adapter (120W, 100-240VAC)
MIL-STD-461 Certified AC Adapter (90W, 115-230VAC)
Vehicle Adapter (120W, 11-32VDC)
Dioitizer Pen

Digitizer Pen
Capacitive Stylus
Protection Film Tablet Hard Handle Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree)

Keyboard Dock

Vehicle Dock Office Dock Spare SSD Kit

## **Bumper-to-Bumper Warranty**

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area.

  13.56MHz Contactless HF RFID / NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™
- iii LF/HF RFID reader option is not Energy Star 8.0 compliant
- Smart card reader, HF RFID reader and
- Smart card reader, HF KHID reader and fingerprint scanner are mutually exclusive options. Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11 mm (H), 0.20 kg.

  MIL-STD-461G 90W AC adapter sold separately. Available with limited configurations.

- viii Drop test results vary from configurations and optional accessories.
- Tested by an independent third-party test lab following MIL-STD-810H.

  FHD webcam and optional Windows Hello
- face-authentication camera (front-facing) are mutually exclusive options. Available when barcode reader option is selected.
- xii Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and

# Fully Rugged **Tablet**



## **Docking Solutions**

3				
	Vehicle Dock for Tablet Mode	Vehicle Dock for Laptop Mode	Office Dock for Tablet Mode	Office Dock for Laptop Mode
Serial Port	1	1	1	1
VGA	1	1	1	1
Microphone			1	1
Audio Output			1	1
DC in Jack	1	1	1	1
USB	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 3 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3	USB 2.0 x 2 USB 3.2 Gen1 x 3
LAN	2	2	2	2
HDMI	1	1	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	3 (WWAN, WLAN, GPS)		
Kensington Lock	1	1	1	1

# Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved ation provided herewith is for reference only available specification shall be subjected to quotation by request. V01M04Y21WW