



















B360 3D demo

B360 PRO FULLY RUGGED NOTEBOOK

- MIL-STD 810H, 6ft operating drop rating, IP66 certified and optional salt fog resistant
- 10th Generation Intel® Core™ Processor
- 13.3" FHD LumiBond® display with Getac sunlight readable technology (1,400 nits) and capacitive touchscreen
- Optional NVIDIA® GeForce® GTX1050 4GB discrete graphic controller
- Enhanced enterprise security with optional dual user replaceable storage, Windows Hello face-authentication camera, integrated 1D/2D imager barcode reader and multi-factor authentication options
- LifeSupport™ battery swappable technology



SPECIFICATIONS

Operating System

Windows 10 Pro Windows 11 Pro

Mobile Computing Platform

Intel® Core™ i5-10210U Processor 1.6GHz Max. 4.2GHz with Intel® Turbo Boost Technology 6MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-10310U vPro™ Processor 1.7GHz Max. 4.4GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel® Core™ i7-10610U vPro™ Processor 1.8GHz Max. 4.9GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

Intel[®] Core[™] i7-10710U Processor 1.1GHz Max. 4.7GHz with Intel[®] Turbo Boost Technology 12MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics Optional: NVIDIA® GeForce® GTX1050 4GB discrete graphics controller

Display
13.3" IPS TFT LCD FHD (1920 x 1080)
Protection film

1,400 nits LumiBond® display with Getac sunlight readable

Storage & Memory 8GB DDR4 Optional: 16GB / 32GB / 64GB DDR4 256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD Optional 2nd Storage ^N: 256GB / 512GB / 1TB SATA SSD

Keyboard

LED backlit membrane keyboard Optional: LED backlit rubber keyboard

Pointing Device

Capacitive multi-touch screen

Touchpad - Touchpad with two buttons

Expansion Slots

Smart card reader x 1 Optional: Discrete graphics controller, or PCMCIA Type II, or ExpressCard/54 ^{II} Optional: 1D/2D imager barcode reader

Multimedia Bay

Optional: DVD super multi drive / Blu-Ray super multi drive

I/O Interface

FHD webcam x 1 Audio in/out combo x 1

DC in Jack x 1
PowerShare USB 2.0 x 1
USB 3.2 Gen 2 Type-A x 2
LAN (RJ45) x 1
HDMI 1.4 x 1

Docking connector x 1
Optional: SIM card slot x 1 (Mini-SIM, 2FF)
Optional: Windows Hello face-authentication camera

(front-facing) x 1 Optional: RF antenna pass-through for GPS, WWAN and

WLAN

Configurable I/O options *i : 1. Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1

Sub) x 1 2. Serial port (9-pin; D-sub) x 1 + USB 3.2 Gen 2 Type-C x 1 3. Serial port (9-pin; D-sub) x 1 + Display port x 1 4. Serial port (9-pin; D-sub) x 2 + External VGA (15-pin; D-

. Serial port (9-pin; D-sub) x 2 + USB 3.2 Gen 2 Type-C x 1

6. Serial port (9-pin; D-sub) x 2 + Display port x 1 7. Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1 + 2nd LAN (RJ45) x 1 Serial port (9-pin; D-sub) x 1 + Display Port x 1 + 2nd LAN

Communication Interface 10 / 100 / 1000 base-T Ethernet Intel® Wi-Fi 6 AX200, 802.11ax

Bluetooth (v5.2) viii Optional dedicated GPS viiii

Optional: 4G LTE mobile broadband with integrated GPS viii, ix

Security Features

POWEY
AC adapter (90W, 100-240VAC, 50/60Hz)
AC adapter (120W, 100-240VAC, 50/60Hz)
High capacity Li-ion battery (10.8V, typical 6900mAh; min.
6600mAh) x 2
LifeSupport™ battery swappable technology

Dimension (W x D x H) & Weight 342 x 281 x 53.5mm (13.46" x 11.06" x 2.11") 3.08Kg (6.79lbs) xii

Rugged Feature

MIL-STD-810H certified IP66 certified

IP66 certified [™]
WIL-STD-461G certified [™]
Vibration & 6ft (1.8m) drop resistant
Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2,
Groups A, B, C, D) [™]
Optional: Salt fog certified

Environmental Specification

Temperature **:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed software

Getac Utility Getac Geolocation Getac Barcode Manager ** Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility
Getac Device Monitoring System (GDMS)
Getac VGPS Utility xviii

High capacity Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh)

AC adapter (90W, 100-240VAC) Capacitive stylus with tether

100W Type-C adapter xxiii

Ontional:

Optional:
Carry bag
High Capacity Li-ion Battery (10.8V, typical 69
6600mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (90W, 100-240VAC)
AC adapter " (120W, 100-240VAC)
MIL-STD-461 AC adapter (90W, 100-240VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Capacitive stylus with tether
Protection film
Vehicle cradle acity Li-ion Battery (10.8V, typical 6900mAh; min. Vehicle cradle Vehicle dock Office dock Spare SSD kit

Vehicle Dock Office Dock Serial Port 2 2 External VGA 1 1 Microphone 1 1 **Audio Output** 1 1 DC in Jack 1 1 USB 6 5 LAN 2 2 HDMI 13 1 1 RF Antenna Connector 3 (GPS, WWAN, WLAN)

B360 PRO FULLY **RUGGED NOTEBOOK**

Bumper-to-Bumper warranty
Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.
That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.
Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- From 14th October 2025, Windows 10 Pro is going to End of Service. Windows 10 Pro will not be upgradable to Windows 11 Pro and will no longer be eligible to receive Microsoft security updates. Discrete graphics card, PCMCIA slot, and Expresscard slot are mutually exclusive.
 HF(13.56MHz) combo HF RFID/NFC reader (iClass, HID Prox, ISO 15693, 14443 A/B, Mifare and FeliCaTM compliant).
 Second storage is optional and will be fitted with a removable cover when not chosen at point of purchase.

- purchase. DVD super multi drive and Blu-Ray super multi drive

- DVD super multi drive and Blu-Ray super multi drive are mutually exclusive. External VGA, USB 3.2 Gen 2 Type-C port and Display port are mutually exclusive. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Units with 4G LTE option comes with an embedded SIM card slot.
- \/|||
 - SIM card slot.
- Fingerprint reader and HF RFID reader are mutually Χ. ringerprint reader and the Krib reader are middle exclusive. 120W AC adapter is used for office dock and for device configured with discrete graphics card. XI.
- XII. Weight and dimensions vary from configurations and optional accessories. MIL-STD-461 90W AC adapter sold separately. Available with limited configurations and

- Available with inflied community and environment conditions.
 Tested by an independent third-party test lab following MIL-STD-810H.
 Available when barcode reader option is selected.
 Models require either embedded or standalone GPS
- XVI. XVII. module XVIII.
- Do not support the configurations with discrete graphics card.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



THIRD WAVE RUGGEDTECH PVT. LTD.

B-4, Chaitanya, Opp. Maradia Plaza, C.G. Road, Ahmedabad, 380006, Gujarat, India Tel:- +91 93282833304

Web: www.thirdwaverugged.com Email: info@thirdwaveruggedtech.com

AHEMDABAD | DELHI | BANGALORE | PUNE | HYDERABAD | CHENNAI





5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 115018, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com I

www.getac.com Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.